



## VST02



Series	Size	P.R.	L.I./S.R.	Load Range	Standard Rim	Section Width(inch)	Overall Diameter(inch)	Max Load(LBS) Single	Max Load(LBS) Dual	Max Pressure Single	Max Pressure Dual	Tread Depth(32nds)
80	ST235/80R16	14PR	129/125L	G	6.50J	9.25	30.8	4075	3635	110	110	11.97
85	ST235/85R16	14PR	132/127L	G	6.50J	9.25	31.7	4405	3850	110	110	11.97

## VOYAGER S600



Series	Size	P.R.	L.I./S.R.	Load Range	Standard Rim	Section Width(inch)	Overall Diameter(inch)	Max Load(LBS) Single	Max Load(LBS) Dual	Max Pressure Single	Max Pressure Dual	Tread Depth(32nds)
90	ST225/90R16	14PR	123/121M	G	6.00G	8.8	31.7	3330	3175	102	102	13.48





## VN7000



Series	Size	P.R.	L.I./S.R.	Load Range	Standard Rim	Section Width(inch)	Overall Diameter(inch)	Max Load(LBS) Single	Max Load(LBS) Dual	Max Pressure Single	Max Pressure Dual	Tread Depth(32nds)
75	ST205/75R14	6PR	100/96L	C	5.50J	8.0	26.1	1764	1565	50	50	8.19
	ST205/75R14	8PR	105/101L	D	5.50J	8.0	26.1	2039	1819	65	65	8.19
	ST205/75R15	6PR	101/97L	C	5.50J	8.0	27.1	1819	1609	50	50	8.19
	ST205/75R15	8PR	107/102L	D	5.50J	8.0	27.1	2149	1874	65	65	8.19
	ST215/75R14	6PR	102/98L	C	6.00J	8.5	26.7	1874	1653	50	50	8.19
	ST225/75R15	8PR	113/108L	D	6.00J	8.8	28.3	2535	2205	65	65	8.19
80	ST225/75R15	10PR	117/112L	E	6.00J	8.8	28.3	2833	2469	80	80	8.19
	ST175/80R13	6PR	91/87L	C	5.00J	7.0	24.0	1356	1201	50	50	8.19
85	ST235/80R16	10PR	123/119L	E	6.50J	9.3	30.8	3417	2998	80	80	8.19
	ST235/85R16	10PR	125/121L	E	6.50J	9.3	31.7	3638	3197	80	80	8.19

## V7000



Series	Size	P.R.	L.I./S.R.	Load Range	Standard Rim	Section Width(inch)	Overall Diameter(inch)	Max Load(LBS) Single	Max Load(LBS) Dual	Max Pressure Single	Max Pressure Dual	Tread Depth(32nds)
75	ST205/75R14	8PR	105/101L	D	5.50J	8.0	26.1	2039	1819	65	65	9.83
	ST205/75R15	8PR	107/102L	D	5.50J	8.0	27.1	2149	1874	65	65	9.83
	ST215/75R14	6PR	102/98L	C	6.00J	8.5	26.7	1874	1653	50	50	9.83
	ST225/75R15	10PR	117/112L	E	6.00J	8.8	28.3	2833	2469	80	80	9.83
80	ST175/80R13	6PR	91/87L	C	5.00J	7.0	24.0	1356	1201	50	50	9.20
	ST235/80R16	10PR	123/119L	E	6.50J	9.3	30.8	3417	2998	80	80	10.1
	ST235/80R16	12PR	126/122L	F	6.50J	9.3	30.8	3750	2305	95	95	10.1